


Due to their resistance to oxidation, STAIRTEC SE anodized aluminum stair nosing profiles enhance indoor and outdoor installations.


The non-slip, ribbed tread profile section is available with a rounded or squared angle, perfect for retrofitting damaged stairs and concealing edge imperfections. The profile may be fastened with flathead screws or appropriate adhesive.







# stairtec SE



### STAIRTEC SE 40 A\*N Extruded Anodized Aluminum

This anodized aluminum profile with carved internal cavity soundly adheres to pre-existing stairs.

Available in three finishes: silver (AS), gold (AO), bronze (ABN). The silver version is recommended for high traffic areas; the gold and silver are recommended for low traffic areas.

	BxH = in	mm		Art.	
Material:	1-9/16x1-9/16	40x40	SE	40	ASN
Extruded Anodized Aluminum	1-9/16x1-9/16	40x40	SE	40	AON
Finish*: Silver (ASN), Gold (AON), Bronze (ABN)	1-9/16×1-9/16	40×40	SE	40	ABN
Length: 8'10" (2.70meters)					

# STAIRTEC SE 42 A\*N Extruded Anodized Aluminum

This stair nosing profile is equipped with a slightly rounded edge and grooved top surface.

Available in three finishes: silver (AS), gold (AO), bronze (ABN). The silver version is recommended for high traffic areas; the gold and silver are recommended for low traffic areas.

Material: Extruded Anodized Aluminum Finish*: Silver (ASN), Gold (AON), Bronze (ABN)	1-21/32x7/8 1-21/32x7/8 1-21/32x7/8	42×22 42×22 42×22	SE SE SE	42 42 42	ASN AON ABN
Length: 8'10" (2.70meters)					

## STAIRTEC SE 45 A\*N Extruded Anodized Aluminum

This stair nosing profile is equipped with a slightly rounded edge and grooved top surface. The carved internal cavity soundly adheres to pre-existing stairs. Available in three finishes: silver (AS), gold (AO), bronze (ABN). The silver version is recommended for high traffic areas; the gold and silver are recommended for low traffic areas.

Material: Extruded Anodized Aluminum Finish*: Silver (ASN), Gold (AON), Bronze (ABN)	1-25/32×1-19/64 1-25/32×1-19/64 1-25/32×1-19/64	45x33 45x33 45x33	SE SE SE	45 45 45	ASN AON ABN
Length: 8'10" (2.70meters)					