

## Dynamic

<b>Tuft gauge</b>	1/10 loop pile		ISO 2424
<b>Pilecomposition</b>	100% PA SDN		ISO 2424
<b>Primary Backing</b>	Woven		ISO 2424
<b>Secondary backing</b>	AB		ISO 2424
<b>Width</b>	400 cm, 500 cm	± 1%	EN 986
<b>Pile Weight</b>	720 gr/m <sup>2</sup>		ISO 8543
<b>Total weight</b>	1550 gr/m <sup>2</sup>	± 15%	ISO 8543
<b>Pile height</b>	3 mm		ISO 1765
<b>Total Height</b>	5 mm		ISO 1765
<b>Number of knots</b>	197500/m <sup>2</sup>	-7.5% .+10%	ISO 1763
<b>Fire Classification</b>	Cfl-S1		EN 13501-1
<b>Thermal resistance</b>	0.076 M <sup>2</sup> KW		ISO 8302
<b>Light fastness</b>	≥ 5		105-B02
<b>Wearebility</b>	≥ 4		105-X12
<b>Water fastness</b>	≥ 4		105-E01
<b>Electrostatic charging</b>	<2 kV		ISO 6356
<b>Luxury class</b>	LC1		EN 1307
<b>Pictures</b>	www.condorcontract.com		

## Floorsymbols



## Certificates



www.blauer-engel.de/uz128

