



VARIOTEC DC profiles' innovative design elegantly rotates and adapts to match different floor elevations. By simply rotating its shape, this profile can adapt to floor thicknesses ranging from 9/32" to 17/32" (7 to 14mm). Use our adhesive for on-site installation.

variotec DC



VARIOTEC DC 22 OL Polished Brass

Due to its unique shape and the intrinsic qualities of the material, this brass profile guarantees resistance to chemical and mechanical stress and wear. It is used indoors and outdoors, particularly suitable for areas with heavy, industrial traffic as well as for elegant residential detailing. Moisture and corrosive agents may oxidize the exposed surfaces. Buffing the profile with conventional polisher will bring back its shine in no time.

	B = in	mm	Art.		
Material: Extruded Brass	7/8	22	DC	22	OL
Finish: Polished (OL)					
Length: 8'10" (2.70meters)					

VARIOTEC DC 22 A* Anodized Aluminum

This profile is available in three finishes: Silver (AS*), gold (AO*), bronze (AB*). Due to the chromatic variations available, it is especially suitable for residential use.

Available in self-adhesive (A*A) and drilled (A*F) versions.

	B = in	mm	DC	22	AS/AO/AB
Material: Extruded Anodized Aluminum	7/8	22	DC	22	AS/AO/AB
Finish*: Silver (AS), Gold (AO), Bronze (AB)					
Length: 8'10" (2.70meters)					