



## GENERAL DESCRIPTION

Junckers Rustic Oil, Colour is an indoor priming and finishing oil product for untreated wooden floors and table-/worktops.

Junckers Rustic Oil, Colour can be used in combination with Rustic Oil, Clear.

## PRODUCT DESCRIPTION

**Product:** Coloured drying urethane oil in low odor solvent.

**Package sizes:** 0.375 and 2.5 litre.

White and black also 0,75 and 5 litre. Cherry also 0,75 litre.

### Colours:

White, Black, Anthracite grey/SpicyPepper, DarkCoco, Mahogany/SylvaRed, Nut/SylvaKet, RawSugar, SmoothRum, Walnut, WildHazel, Cherry, Driftwood Grey.

**Appearance:** Coloured liquid that dries to a transparent coloured surface.

## TECHNICAL DATA

**Coverage:** 10-50 m<sup>2</sup> depending on wood structure and absorption.

### Application tools:

Cloth, brush, roller or lambswool applicator in combination with a nylon scouring pad for all types of surfaces.

For floors a buffing machine mounted with a cloth covered pad helps spreading and removal of surplus liquid.

**Substrate temperature:** Minimum 15° C.

**Dilution:** Delivered ready for use. Dilution is not recommended.

### Drying time at 20° C:

16-24 hours before applying the finishing oil.

Ready for use 24 hours after the finishing treatment.

Fully cured after 3 days.

Do not cover the surface by i.e. carpets or rugs before the oil is fully cured.

By long-term contact with coloured surfaces smudging can occur. This can be prevented by using clear oil as a finishing treatment.

**Cleaning of tools:** White spirit.

**Storage:** 2 years if unopened and stored at 20°C. Once opened the oil will start to form a skin and may harden in the can.

## SYSTEM RECOMMENDATIONS

### Floors, High traffic:

2 coats of Junckers Rustic Oil colour + 1 coat of Junckers Rustic Oil colour or clear or 2 coats of Junckers HP High Performance.

### Floors, Low traffic:

2 coats of Junckers Rustic Oil colour + 1 coat of Junckers Rustic Oil colour or clear or 2 coats of Junckers ProFinish.

### Table-/worktops:

2 coats of Junckers Rustic Oil colour + 2 thin coats of Junckers Rustic Oil colour or clear.

## DIRECTION FOR USE

### Priming untreated/sanded wood:

Ensure that the surface is absolutely clean, dry and free from dust, wax, grease, polish etc. Unevenness, dirt and discolouration can be removed by sanding in the direction of the grain. Final sanding must be with sandpaper grit 100-120. Vacuum sanding dust.

Larger areas are recommended to be divided into smaller areas that can be oiled in 30 minutes. Always keep a wet edge between the areas.

Moisten the surface with a damp cloth. Be sure that the floor is evenly and visibly wetted to avoid a patchy appearance of the staining. Then leave to dry 10-15 minutes.

Stir the oil well before use and prime with 2 coats of Junckers Rustic Oil colour applied wet in wet: Apply one coat of oil and wait up to 30 minutes before applying the second coat. Work the oil for another 30 minutes. Wipe off excess oil. Dried and unabsorbed oil leaves glossy spots on the surface. The surface should appear matt.

Leave to dry for 16-24 hours.

### Finishing with Junckers Rustic Oil colour or clear:

Depending on wanted colour intensity, finish with either coloured or clear oil.

Sand or scour the surface carefully with fine sandpaper grit 180-220 or a green or black nylon pad. Vacuum sanding dust.

On floors, apply 1 coat of Junckers Rustic oil colour or clear. On table-/worktops, apply 2 thin coats of Junckers Rustic oil colour or clear.

Make sure that the surface is saturated and remove surplus oil within 30 minutes with a dry soft cloth and buff the surface to an even finish using a clean cloth under the buffing pad. On floors a buffing machine can be used as well.

Be aware that wood absorbs oil to varying degree and therefore the oiled surface can appear with some colour variation. This is seen very pronounced on spruce.

**Finishing with lacquer - Floors:**

Higher wearability of the floor can be obtained by finishing with lacquer. Choose one of Junckers lacquers according to the recommended systems.

Please note, that its very important the floor is a 100 % saturated with oil before lacquering. If not, there is a risk of discoloration and especially oak may need extra oil.

Screen with a black pad and remove the dust. Apply one coat of lacquer and leave to dry approx. 4 hours.

Apply the final coat of lacquer and leave to dry until fully cured.

**Care and maintenance, oiled surfaces:**

If the existing oil surface is sound and stable the floor can be maintained with Junckers water based Rustic Top Oil.

On floors and table-/worktops, refresh with Junckers Rustic Oil colour or clear, if the surface shows sign of wear. Method as described under "Finishing with Rustic Oil colour or clear".

**Care and maintenance, lacquered floors:**

If the surface is worn through the floor must be sanded and the area must be re-treated with oil and lacquer.

**IMPORTANT!**

Before using the product, read the label on the container carefully and observe the recommended precautionary measures. See Material Safety Data Sheet for detailed information about precautionary measures.

**FURTHER INFORMATION**

**Products:**

F 2.1 - Junckers Rustic Oil clear

F 2.7 - Junckers Rustic Top Oil

F.4.2 - Junckers ProFinish

F 8.5 - Junckers High Performance Commercial