

Patented perimeter profile for LVT floors requiring an expansion gap - the internal 12mm cavity allows the underlying flooring to move more than ± 5/32" (± 4 mm). Eliminates the need for baseboards, guaranteeing the expansion and perimetrical fastening of the floor. May be used as entrance mat framing and in front of sliding doors.

multicliptvt CLP 240





MULTICLIP - LVT CLP 240 A* Anodized Aluminum

Aluminum anodized in silver, gold and bronze, the profiles are particularly versatile and can be matched with all floor surfaces. Assemble with Clip CL 40 P + Aluminum base CLB 60 ANF.

MULTICLIP - LVT CLP 240* High Resistance Wood Laminated Aluminum

Highly resistant wood effect aluminum profiles, with elevated resistant to abrasion, similar to that of tiled surfaces. The elegant and uniform wood covering is also resistant to stains.

Assemble with Clip CL 40 P + Aluminum base CLB 60 ANF.

The covering is resistant to tear and chemicals agents.

	216		
		AL STATE OF	
	By .	A. Carrier	15
The second secon		THE TANKS IN COMME	Part Control

		Art.		Finish	
Material:	CLP	240	AS	Silver	LVI
Extruded Anodized Aluminum	CLP	240	AO	Gold	LVI
Length: 8' 10" (2.70 meters)	CLP	240	AB	Bronze	LVI

Material:	CLP	240	AC	Maple	1
Extruded wood laminated Aluminum	CLP	240	CI	Cherry	E
l on othe 0' 10" /2 70 motors)	CLP	240	FA	Beechwood	İ
Length: 8' 10" (2.70 meters)	CLP	240	NC	Light Walnut	İ
	CLP	240	NS	Dark Walnut	l
	CLP	240	RO	Oak	l
	CLP	240	RD	Decapé Oak	l
	CLP	240	RG	Grey Oak	
	CLP	240	RG	Bleached Oak	l
	CLP	240	RW	Wengé Oak	İ
	CLP	240	WE	Wengé	I