ROUNDCORNER RO is a complete range of rounded corner profiles conceived to protect exposed external corners and conceal chipped tiled corners. Typically used in heavy trafficked commercial and industrial settings, this profile contains internal, shock-absorbing self-adhesive strips.

roundcorner RO





Stainless Steel and Brass Section





ROUNDCORNER RO 25 A11A Self-Adhesive Powder-Coated Aluminum

This aluminum profile is color-coated with a polyurethane powder coat that is UV-resistant. It is equipped with heavy-duty adhesive, ready for installation. The 1" (25mm) corner width meets technical and safety requirements while maintaining aesthetic appeal.

1	10		777
	1		

	AxB = in	mm		Art.			
Material: Powder coated Aluminum	1x1	25x25	RO	25	A11A		
Finish: Pure white							
Length: 8'10" (2.70meters)							

ROUNDCORNER RO 25 A*A Self-Adhesive Anodized Aluminum

This anodized aluminum rounded corner profile is equipped with heavy-duty adhesive, ready for installation. The 1" (25mm) corner width meets technical and safety requirements while maintaining aesthetic appeal.

Material: Extruded Anodized Aluminum	1x1	25x25	RO	25	ASA/AOA/ ABA
Finish: Silver (ASA), Gold (AOA), Bronze (ABA)					
Length: 8'10" (2.70meters)					

ROUNDCORNER RO-ILA Self-Adhesive Polished Stainless Steel

Corner protection stainless steel profile which guarantees high performances of corner protection and hygiene. Especially conceived for public and food processing plants etc.

These profiles can also be made in stainless steel grade AISI 304 or AISI 316.CO 30 is available in the polished version (IL) or brushed (IS).

Thickness RO 25: 1/32" (1mm) Thickness RO 30 / 40 / 50: 1/16" (1.2mm)

Material: Stainless steel	1x1 1-3/16x1-3/16	25x25 30x30	RO RO	25 30	ILA ILA
Finish: Polished (ILA)	1-9/16x1-9/16 2x2	40X40 50X50	RO RO	40 50	ILA ILA
Length: 8'10" (2.70meters)					
Width: 1"-2" (25-50mm)					
Surface with protection film strip					

ROUNDCORNER RO-OLA Self-Adhesive Polished Brass

Available in several sizes, this polished brass rounded corner profile meets technical and safety standards in hospitals, food processing plants and public bathrooms.

Thickness RO 25: 1/32" (1mm)

Thickness RO 30 / 40 / 50: 1/16" (1.2mm)

Material: Laminated brass Finish: Polished (OLA) Length: 8'10" (2.70meters) Width: 1"-2" (25-50mm)	1x1 1-3/16x1-3/16 1-9/16x1-9/16 2x2	25x25 30x30 40X40 50X50	RO RO RO RO	25 30 40 50	OLA OLA OLA OLA
Width: 1"-2" (25-50mm)					
Surface with protection film strip					