


STRIPTEC ST/SB offers a wide selection of transition and threshold strip profiles available in a variety of widths and finishes. Its surface may be smooth or ribbed, curved or flat to fit under doorways. The brass and aluminum models are suitable for high traffic areas.

strip⁺tec ST/STB



STRIPTEC ST 38 A* Anodized Aluminum


Top surface ribbing offers high corrosion resistance and limited resistance to mechanical impact.
Center thickness = 9/64" (3.7mm).
Available in self-adhesive (A*A) and drilled (A*F) versions.



	B = in	mm	Art.	Adhesive	Drilled
Material: Extruded Anodized Aluminum	1-1/2	38	ST 38	ASA	ASF
Finish*: Silver (AS*), Gold (AO*), Bron. (AB*)	1-1/2	38	ST 38	AOA	AOF
			ST 38	ABA	ABF
Length: 8'10" (2.70meters)					
35-7/16" / 4' 5" (0.90/1.35meters)					

STRIPTEC STB-OL* Polished Brass


Brass guarantees excellent resistance to mechanical and chemical impact. This profile is ideal for industrial and commercial heavy-traffic areas as well as elegantly-designed residential spaces.
Center thickness = 1/16" (1.5mm).
Available in self-adhesive (O*A) and drilled (O*F) versions.



	B = in	mm	Art.	Adhesive	Drilled
Material: Extruded Brass	1-3/16	30	STB 30	OLA	OLF
Finish: Polished (OL*)	1-3/8	35	STB 35	OLA	OLF
	1-9/16	40	STB 40	OLA	OLF
Length: 8'10" (2.70meters)					
35-7/16" / 4' 5" (0.90/1.35meters)					

STRIPTEC ST 50 OL* Polished Brass


This heavy, curved brass profile offers excellent resistance to mechanical and chemical impact, making it ideal for industrial and commercial heavy-trafficked areas.
Center thickness = 3/16" (5mm).
Available in self-adhesive (O*A) and drilled (O*F) versions.



	B = in	mm	Art.	Adhesive	Drilled
Material: Extruded Brass	2	50	ST 50	OLA	OLF
Finish: Polished (OL*)					
Length: 8'10" (2.70meters)					

STRIPTEC STB 25 A* Anodized Aluminum


This flat, grooved profile offers high corrosion resistance and limited resistance to mechanical impact. It is available in three finishes: silver (AS), gold (AO), bronze (AB).
Center thickness = 3/32" (2.2mm).
Available in self-adhesive (A*A) and drilled (A*F) versions.



	B = in	mm	Art.	Adhesive	Drilled
Material: Extruded Anodized Aluminum	1	25	STB 25	ASA	ASF
Finish*: Silver (AS*), Gold (AO*), Bron. (AB*)	1	25	STB 25	AOA	AOF
	1	25	STB 25	ABA	ABF
Length: 8'10" (2.70meters)					
35-7/16" / 4' 5" (0.90/1.35meters)					

STRIPTEC STB 35 A* Anodized Aluminum

This flat, heavy-duty profile is available in three finishes: silver (AS), gold (AO), bronze (AB). The drilled version has holes along the center. Lateral holes may be ordered upon request.
Center thickness = 3/32" (2.4mm).
Available in self-adhesive (A*A) and drilled (A*F) versions.



	B = in	mm	Art.	Adhesive	Drilled
Material: Extruded Anodized Aluminum	1-3/8	35	STB 35	ASA	ASF
Finish*: Silver (AS*), Gold (AO*), Bron. (AB*)	1-3/8	35	STB 35	AOA	AOF
	1-3/8	35	STB 35	ABA	ABF
Length: 8'10" (2.70meters)					
35-7/16" / 4' 5" (0.90/1.35meters)					

Pre-cut length available in SELFLINE kit L= 35-7/16" / 4' 5" (0.90/1.35m)